

Product Information

UR1 - / UR2-015..050V M / K

Flow Switch
UR1 / UR2-...V



- Low pressure loss
- Compact design
- Soldered/welded connection


Characteristics


The devices function via the principle of a spring-supported paddle, and the magnetic triggering of a reed switch.

Technical data

| | | |
|---|--|---|
| Switch | reed switch | |
| Nominal width | DN 15..80 | |
| Process connection | soldered/welded nozzle (further process connections available on request) | |
| Switching range | 5..174 l/min | for details see table "Ranges" |
| Q_{max.} | to 600 l/min | |
| Tolerance | ±15 % of full scale value | |
| Pressure | Brass | PN 25 bar (UR1) |
| | Stainless steel | |
| | PVC PPS | PN 10 bar (UR2) |
| Medium temperature | -20..+110 °C (optionally 150 °C) | |
| Ambient temperature | -20..+70 °C | |
| Media | water (oils, gases and aggressive media available on request) | |
| For electrical data see "UR1 Brass switching unit" or "UR1 Plastic switching unit" | see "UR1 Brass switching unit" or "UR1 Plastic switching unit" | |
| Materials medium-contact | <i>Brass construction:</i> CW617N nickelled, CW614N, 1.4310, 1.4301, hard ferrite, NBR | <i>Stainless steel construction:</i> 1.4305, 1.4571, 1.4310, 1.4310, hard ferrite PTFE-coated, FKM |
| | <i>Optional:</i> Body made from POM (PN 10) Body made from PPS (PN 10) | |
| Non-medium-contact materials | see "UR1 Brass switching unit" or "UR1 Plastic switching unit" | |
| Weight | see table "Dimensions and weights" | |

| | |
|------------------------------|---|
| Installation location | Standard: horizontal inwards flow; switching unit not recommended underneath; other installation positions are possible; the installation position affects the switching point and range. |
|------------------------------|---|

| | |
|--------------------------------------|--|
| UR1 Brass switching unit | |
| Wiring | normally open (n.o.) or normally closed (n.c.), no. 0.225  |
| Switching voltage | max. 230 V AC |
| Switching current | max. 1 A |
| Switching cap. | max. 50 VA |
| Protection class | 1 - PE connection |
| Ingress protection | IP 65 |
| Electrical connection | cabl 1.5 m, optionally for round plug connector M12x1, 4-pole |
| Materials, non-medium-contact | CW614N, nickelled, CW614N, NBR, PVC, POM |

| | |
|--------------------------------------|---|
| UR2 Plastic switching unit | |
| Wiring | Normally open (n.o.) 0.446 Normally closed (n.c.) 0.447  |
| Switching voltage | max. 230 V AC |
| Switching current | max. 1 A |
| Switching cap. | max. 50 VA |
| Protection class | 2 - Safety insulation |
| Ingress protection | IP 65 |
| Electrical connection | cabl 1.5 m |
| Materials, non-medium-contact | PA, PVC, POM |

Product Information

UR1 - / UR2-015..050V M / K

Ranges


Details in the table correspond to horizontal inwards flow with decreasing flow rate. UR2 (Plastic switching unit) is adjusted in the factory; please specify switching value.

| DN | Switching range l/min H ₂ O | Types | Q _{max.} recommended |
|-------|---|-----------|----------------------------------|
| DN 15 | 5.0 - 6.5 | UR.-015V. | 20 |
| DN 20 | 10.0 - 15.5 | | 40 |
| DN 25 | 11.0 - 13.0 | UR.-025V. | 80 |
| DN 32 | 26.0 - 33.0 | | 100 |
| DN 40 | 37.0 - 42.5 | | 150 |
| DN 50 | 47.5 - 60.0 | UR.-050V. | 200 |
| DN 65 | 95.0 - 117.0 | | 400 |
| DN 80 | 147.0 - 179.0 | | 600 |

Special ranges are available.

Dimensions and weights

| DN | Types | H | D | A | B | Weight kg | |
|-----------|-----------|------|----|----|----|--------------|------|
| | | | | | | UR1 | UR2 |
| DN 15..20 | UR.-015V. | 18.0 | 13 | - | - | 0.25 | 0.20 |
| DN 25..50 | UR.-025V. | 27.5 | - | 12 | 16 | | |
| DN 50..80 | UR.-050V. | 42.0 | | | 19 | | |




Handling and operation

Note

- Include straight calming section of 5 x DN in inlet and outlet
- If the media are dirty, install a filter (use magnetic filter for ferritic components).
- It must be ensured that the values given for voltage, current, and power are not exceeded.
- When switched on, a load must be connected in series.
- The electrical details apply to ohmic loads. Capacitive, inductive and lamp loads must be operated using a protective circuit.

Adjustment

UR1 - loosen bolts, push the switching current tube into the desired position. Retighten the bolts. Normally closed (n.c.) or normally open (n.o.) as per table "Technical data"



Ordering code

1. 2. 3. 4. 5.
UR - V

○=Option

| | |
|----------------------------------|--|
| 1. Switching unit | |
| 1 | brass |
| 2 | ○ plastic (already adjusted, specify switching value and normally closed (n.c.) or normally open (n.o.)) |
| 2. Nominal width | |
| 015 | DN 15..25 |
| 025 | DN 25..40 |
| 050 | DN 50..80 |
| 3. Process connection | |
| V | soldered/welded nozzle |
| 4. Connection material | |
| M | brass |
| K | stainless steel |
| 5. Switching unit options | |
| A | for switching unit ATEX A-U1.1 The switching head is ordered in addition. |
| S | ○ for round plug connector M12x1, 4-pole |

Options

- Switching ranges for oil or gas
- Special quantity
- Adhesive PVC fitting

Ordering information

- Specify direction of flow, medium, and switching range, UR1 or switching value UR2.
- For UR2 specify normally closed (n.c.) or normally open (n.o.).
- For oils, state viscosity, temperature and designation (e.g. ISO VG 68) (enquire about range).
- For gases, state pressure (relative or absolute), temperature and medium (e.g. air) (enquire about range).