


GB110



► Type GB110



Belt expansion joint with one or more arches

Design: Cylindrical, single or multi-arch elastomer or multilayer expansion joint with sleeves for clamped fixing, ideally only for round or oval duct cross sections
 Optional expansion joint with installation seam
 Optional external pressure support rings in the arch trough
 Optional vacuum support rings

Installation method: Clamped fixing at duct level

Dimensions: For round and oval duct cross sections of up to approx. \varnothing 1500 mm

Installation length: = Installation gap + 2x fixing width
 Individually according to customer specifications

Fixing width: Depends on pressure, nominal diameter and clamp design at least 40 mm

Media temperature: Suitable for up to 400°C

Pressure: Up to ± 0.25 bar. Higher pressures on request

Movement: For axial, lateral and angular movements
 Benchmarks:
 axial compression = approx. 0.25 x installation gap
 axial extension = approx. 0.25 x installation gap
 lateral displacement = approx. 0.20 x installation gap
 In the event of axial extension and simultaneous lateral displacement, movements are reduced
 In the event of axial extension or vacuum, the expansion joint can be pulled from the pipeline (provide groove at end of pipeline if needed)
 For large lateral movements, we recommend presetting the duct against the direction of movement

Application:
 Power plants, waste incineration plants, gas turbines, cement factories, paper industry, steel industry e.g. in exhaust pipes, in ventilators, in air ducts, in ash lines, in filter systems



Expansion joint variants

	Elastomer expansion joint	Multilayer expansion joint
Temperature:	up to 200°C	up to 400°C
Design:	Single-layer elastomer expansion joint fully joined with one or more fabric reinforcement inserts	Multilayer fabric expansion joint consisting of interior insulating layers, embedded sealing films and exterior pressure carrier fabrics.
Material:	<p>Rubber grades: up to 100°C: EPDM, IIR, CSM, NBR up to 180°C: FPM up to 200°C: Silicon (Q)</p> <p>PTFE lining: Permanently embedded on the inside at the rubber bellows in order to withstand corrosive chemical attack, available starting at NB 300</p> <p>Inserts: Nylon, polyester, Kevlar, glass fibre, and steel mesh</p>	<p>Internal layers: PTFE glass fibre fabric laminate, glass fibre fabric, glass mat, silicate fabric</p> <p>Sealing films: PTFE film, stainless steel film</p> <p>External layer: Silicon coated glass fibre fabric PTFE-glass fibre fabric laminate</p>

Fastening clamps

Design: Depending on pressure and nominal diameter, endless clamp belt or hinge bolt clamps
 At higher pressures, 2 adjacent clamps per fastening side

Width: Endless clamp belt: $\frac{3}{4}$ "
 Hinge bolt clamp: depending on \varnothing : 18–30 mm

Materials: Endless clamp belt with screw lugs (tongs): 1.7300
 Hinge bolt clamp, belt and housing: 1.4016 (Screw steel galvanised)

Optional accessories

Support rings: Vacuum support rings inside in the arch apex and/or external pressure support rings in the arch trough

Installation set: Tools and aids for punching and closing the expansion joint seam

Planning help GB110

